

COALA CLING FILM WHITE S



MATERIAL DESCRIPTION

Coala Cling Film White S is an electrostatic white gloss monomeric PVC film with excellent printing results using Eco-Solvent, Solvent and UV printers. Laminated with a one-sided clay-coated paper (180 g/m²).

PRINTER & INK COMPATIBILITY



FILM THICKNESS

150
μ

PRODUCT STRUCTURE

- Support: 150 mic monomeric, electrostatic PVC film (Cling Film)
- Liner: One-sided clay-coated paper (180 g/m²)
- Dimensional Stability MD Shrinkage < 0,4mm FTM 14
- Tensile strength md > 20 MPa (DIN EN ISO 527)
- Tensile strength cd > 20 MPa (DIN EN ISO 527)
- Elongation md > 300 % (DIN EN ISO 527)
- Elongation cd > 350 % (DIN EN ISO 527)

DURABILITY

- Durability: 1 year (unprinted material)
- Application temperature: min. 10°C
- End-Use Temperature range: from -40°C to +90°C

APPLICATIONS

- Short-term advertising on smooth and polished surfaces

BENEFITS

- Very good flatness characteristics
- Excellent dimensional stability and enhanced image brightness
- If applied properly, no adhesive residues will be left

SHELF LIFE STORAGE AND CONDITIONS



- 2 years when stored in the original packaging between 20°C and 25°C at 50 % relative humidity.

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material. Antalis cannot be responsible for any damage to the printer caused by printing our media.



COALA CLING FILM WHITE S



antalis ^{TEAM}
Just ask Antalis