



COALA DOUBLE SIDE TEXTILE

Product Information

270 g polyester for Double sided banners
One side a special polymer coating
Identical surface front and back side
Special white polymer coating on both sides
High print brilliance
Print on both sides with different motives
Completely opaque
Ideal for doublesided advertising
Prints great with Solvent, UV and Latex Ink
B1 fire resistant
Oeko tex, PVC Free

Technical data

Product:	Coala Double side Textile	Unit	Standard
Substrate	100 % Polyester		DIN 6001
Ends / Picks	21 / 17	Fd / cm	DIN 1049-2
Yarn	334 /334	dtex /Nm	DIN ISO 2060
Weave	Plain weave		DIN ISO 9354
Grammage	270 ± 25	g/m ²	DIN ISO 2286-2
Thickness	0,30 ± 0,03	mm	DIN ISO 2286-3
Tensile strength warp/weft	> 125 / 80	daM/5cm	DIN ISO 13934-1
Tear resistance warp/weft	> 45 / 65	[N]	DIN ISO 13937-1
Whiteness	≥ 90		Berger
Light fastness	≥ 5-6	Grade	DIN ISO 105-B02
Water pressure test	> 1000	mm	DIN 20811 ISO 811 or DIN 53886
Air Permeability	0	l / dm ²	DIN 4102 B1 or DIN 53887
Flame Retardant	B1		DIN 4102 B1 NFPA 701, CA 1237

Standard Dimensions

1520 mm x 50 m



The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.





The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.

