

Specifications Cordstrap D-Connect Dunnage Bags: Cargo Secure Medium 90 x 120 cm / 36" x 48"

Performance Specifications	
Working Pressure	0,2 Bar / 20 kPa / 2.90 Psi
Burst Pressure*	0,6 Bar / 60 KPa / 8.70 Psi
AAR Level	1
Complying to AAR PPPD-Standard:	AAR Certified Level 1

Product Specifications	
Dimensions**	90 x 120 cm – 36" x 48"
Valve Type	Fast Inflation Valve - Direct Connect
Material	
Bag Outer layer(s)	Woven Polypropylene
Bag Inner layer	Polyethylene
Valve System	Polyethylene fitments and Silicone
Color of Bag	White with Red Printing
Color of Valve	Black with Red Cap
Color of Label	Orange
Packaging	
Pieces per box***	400 pieces
Box Dimensions**	1000 x 1200 x 960 mm – 39.4" x 47.2" x 37.8"
Box Weight**	196 kg – 432 lbs
Product Code	4270110
Packaging (small box)	
Pieces per box***	30 pieces
Box Dimensions**	1200 x 333 x 350 mm – 47.2" x 13.1" x 13.8"
Box Weight**	16,2 kg – 35.9 lbs
Product Code	4271110

Recommended Inflators	
Product	D - Connect Fast Inflator
Product Code	4870000
Product	D - Connect Fast Inflator HD
Product Code	4870051
Product	D - Connect Digital Fast Inflator
Product Code	4855900 & 4855903

* In a void of 300 mm / 12"

** Tolerance of 5%

*** Tolerance of 2%

We recommend storing all Cordstrap Products in a cool a dry environment out of direct sunlight and between -5°C and 40°C / 23°F and 104°F

All information provided is based on accuracy at time of creation



Represented in over 50 countries

World market leader

ISO 9001:2008 certified

Manufacturer & supplier since 1965

Offering genuine customer solutions

Specialist advice

Continued product development

Training at Cordstrap Training Centers

Quality assurance